

PX0798/P/BL2 Datasheet

Product Name // Bulkhead Flange Mount Connector
PX0798 Series 12 Contact Plug Crimp/Solder Termination
(Contacts Available Separately) Blue Insert


 [View Product Page](#)




// Product Description:	
<ul style="list-style-type: none">Bulkhead Flange Mount ConnectorsWater and dustproof to IP68 when mated with compatible connectorScrew fixing flange, supplied with sealing gasket and screw sealing grommetsPlug or Socket2, 3, 4, 6, 7, 9, 12, 25 Contact with leading Earth contact on 3 Contact Socket versionsScrew, Crimp, Crimp/Solder Terminations available, depending on part code and number of Contacts	<ul style="list-style-type: none">Screw contacts supplied fitted, Crimp contacts supplied loose (Crimp/Solder contacts and fitting tools available separately)Choice of coloured inserts to enable positive visual identification of connector:Part codes suffixed with a colour code followed by 2 have that colour insertColour choices and colour codes: Blue (BL), Green (GN), Grey (GY), Light Grey (LG), Red (RD), White (WH), Yellow (YL), Black (standard colour, no suffix code)PX0733 Sealing Cap available separately to maintain IP rating of unmated connectorsMate with PX07 Series Flex Connectors

// General Information:	
<p>Product Display Title:</p> <p>Product Family:</p> <p>Product Series:</p> <p>Approvals:</p> <p>Body Material:</p> <p>Contact Type:</p> <p>Coupling Type:</p> <p>Current Max:</p> <p>Diameter Over Coupling Ring Mm:</p> <p>Flamability Rating:</p> <p>Function:</p> <p>Insert Colour:</p> <p>Ip Rating:</p> <p>Max Operating Temperature:</p> <p>Min Operating Temperature:</p> <p>Number Of Contacts:</p> <p>Voltage Max:</p>	<p>Bulkhead Flange Mount Connectors</p> <p>Circular Power Connectors</p> <p>Standard Buccaneer</p> <p>CSA, UL, VDE</p> <p>Polyamide (PA)- Glass Filled</p> <p>Plug Contact</p> <p>Screw</p> <p>5A</p> <p>38.1mm</p> <p>UL94HB</p> <p>Bulkhead Flange Mount Connector</p> <p>Blue Insert</p> <p>IP68, IP69K</p> <p>+70°C</p> <p>-20°C</p> <p>12 Contacts</p> <p>50V</p>

// Product PDF Links

 Standard Series power connectors...

 Standard Series power connectors...