# PX0931/05/P Datasheet



## Product Name // Panel Mount Connector PX0931 Series 5 Contact Plug

View Product Page

 $R21.5 \xrightarrow{5.5} \emptyset 50.0$  I = 15.0 MAX I = 15.0 MAX

## // Product Description:

- O Panel Mount Connector
- Water and dustproof to IP68 when mated with compatible connector
- O Positive fast-acting locking ring can be turned with a gloved hand
- O Plug or Socket
- 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- O Single hole fitting, anti-rotation key
- O Panel thickness 3mm-7mm
- O Supplied with high grade sealing gasket
- O PX0970/PX0992 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with PX0911 and PXA911 Series Flex Connectors

### // General Information:

**Product Display Title: Product Family: Product Series:** Approvals: **Body Material: Body Material Type:** Contact Type: Coupling Type: **Current Max:** Diameter Over Coupling Ring Mm: Flamability Rating: Function: Ip Rating: Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:

Panel Mount Connector **Circular Power Connectors** 900 Series Buccaneer CSA Polyamide (PA) Plastic Body **Plug Contact** Screw 25A 58mm UL94V-0 Front Panel Mount Connector IP68 14AWG 10AWG 4mm2 2.5mm2 +85°C -40°C 5 Contacts 600V

#### // Product PDF Links

900 Series power connectors...

900 Series power connectors wiring...

// Product 3D CAD Model Links

PX0931/05/P3D CAD Model