


# PXM7010/32P/CR/0709/SN Datasheet



**Product Name // Flex Cable Connector PXM7010 Series 32**  
**Contact Plug Crimp/Solder Termination (contacts available**  
**separately) 7mm-9mm Cable (White Gland) Metal Body With**  
**Braid Termination**

[View Product Page](#)



**// Product Description:**

- Flex Cable Connectors
  - Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
  - Quick turn locking ring with less than quarter turn locking and positive feedback
  - Plug or Socket
  - 2, 3, 6, 10, 32 Contact with leading Earth contact on 3 Contact versions
  - Screw, Crimp/Solder terminations available, depending on part code; Screw contacts supplied fitted, Crimp/Solder contacts and fitting tools available separately
  - Choice of body material depending on part code:
- Plastic body (part codes prefixed PXP)
  - Metal body (part codes prefixed PXM). Cable Braid Termination option supplied with part codes suffixed /SN or available separately (part code PXM7090)
  - Choice of cable acceptance 5mm-15mm diameter depending on part code (see data for details)
  - PXP7088 Series Gland Packs available separately to accomodate all sizes
  - PXP7081/PXM7081 Sealing Cap available separately to maintain IP rating of unmated connectors
  - Mate with PXP7011/PXM7011 Series Inline and PXP7012/PXM7012 Series Front Panel Mount Connectors

**// General Information:**

Product Display Title:	Flex Cable Connectors
Product Family:	Circular Power Connectors
Product Series:	7000 Series Buccaneer
Approvals:	UL
Body Material:	Zinc Alloy - Nickel Plated
Body Material Type:	Metal Body With Braid Termination
Contact Type:	Plug Contact
Coupling Type:	Bayonet Lock
Current Max:	3A
Diameter Over Coupling Ring Mm:	42mm
Flamability Rating:	UL94V-0
Function:	Flex Cable Connector
Ip Rating:	IP66
Max Cable Entry Size:	9mm
Min Cable Entry Size:	7mm
Max Contact Accomodation Awg:	26AWG
Min Contact Accomodation Awg:	22AWG
Max Contact Accomodation Mm2:	0.34mm2
Min Contact Accomodation Mm2:	0.14mm2
Max Operating Temperature:	+120°C
Min Operating Temperature:	-40°C
Number Of Contacts:	32 Contacts
Voltage Max:	600V

**// Product PDF Links**

7000 Series power connectors...

7000 Series metal body power...

**// Product 3D CAD Model Links**

PXM7010/32P/CR/0709/SN3D CAD Model