


# PXP7011/06P/ST/0709 Datasheet

**Product Name** // Inline Cable Connector PXP7011 Series 6  
**Contact Plug Screw Termination (contacts supplied fitted)**  
**7mm-9mm Cable (White Gland) Plastic Body**

 [View Product Page](#)





// **Product Description:**

- Inline Cable Connectors
  - Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
  - Quick turn locking ring with less than quarter turn locking and positive feedback
  - Plug or Socket
  - 2, 3, 6, 10, 32 Contact with leading Earth contact on 3 Contact versions
  - Screw, Crimp/Solder terminations available, depending on part code; Screw contacts supplied fitted, Crimp/Solder contacts and fitting tools available separately
  - Choice of body material depending on part code:
- Plastic body (part codes prefixed PXP)
  - Metal body (part codes prefixed PXM). Cable Braid Termination option supplied with part codes suffixed /SN or available separately (part code PXM7090)
  - Choice of cable acceptance 5mm-15mm diameter depending on part code (see data for details)
  - PXP7088 Series Gland Packs available separately to accomodate all sizes
  - PXP7082/PXM7082 Sealing Cap available separately to maintain IP rating of unmated connectors
  - Mate with PXP7010/PXM7010 Series Flex Connectors

// **General Information:**

Product Display Title:	Inline Cable Connectors
Product Family:	Circular Power Connectors
Product Series:	7000 Series Buccaneer
Approvals:	UL
Body Material:	Polycarbonate/Polybutylene Terephthalate (PC/PBT)
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Bayonet Lock
Current Max:	10A
Diameter Over Coupling Ring Mm:	42mm
Flamability Rating:	UL94V-0
Function:	Inline Cable Connector
Ip Rating:	IP66
Max Cable Entry Size:	9mm
Min Cable Entry Size:	7mm
Max Contact Accomodation Awg:	17AWG
Min Contact Accomodation Awg:	17AWG
Max Contact Accomodation Mm2:	1mm2
Min Contact Accomodation Mm2:	1mm2
Max Operating Temperature:	+120°C
Min Operating Temperature:	-40°C
Number Of Contacts:	6 Contacts
Voltage Max:	600V

// **Product PDF Links**

-  7000 Series power connectors...
-  7000 Series plastic body power...

// **Product 3D CAD Model Links**

-  PXP7011/06P/ST/07093D CAD Model



Have a question or project enquiry  
you'd like to talk to us about?



[Click Here To Contact Us](#)